



**SLATE
SOLUTIONS**

SLSIIIA

Soft Armor



SHOWN IN DELTA CUT

FEATURES

- ◇ The SLS ballistic package stands out as one of our top-performing yet cost-effective options. It's an ideal selection for officers seeking the optimal balance of comfort, value, and flexibility within a 100% aramid hybrid design.
- ◇ Covered with a 70d Nylon Rip Stop with TPU backing, heat sealed material.

Specifications

Threat Level (NIJ 06)	IIIA
Certification Sizes	C1 - C5
Weight (AD)	1.18 psf
Thickness (in)	0.25" (6.35mm)

Certification Test Results

V50 - 357sig 125gr FMJ (new)	1867 ft/s (569 m/s)
V50 - 357sig 125gr FMJ (conditioned)	1796 ft/s (547 m/s)
P-BFS Avg. - 357sig 125gr FMJ	27.3 mm
V50 - 44mag 240gr SJHP (new)	1661 ft/s (506 m/s)
V50 - 44mag 240gr SJHP (conditioned)	1613 ft/s (492 m/s)
P-BFS Avg. - 44mag 240gr SJHP	36 mm

Special Threat Testing

V50 - 2gr RCC	3060 ft/s (932m/s)
V50 - 4gr RCC	2642 ft/s (805m/s)
V50 - 16gr RCC	2244 ft/s (684m/s)
V50 - 17gr FSP (.22cal)	2017 ft/s (615m/s)
V50 - 64gr RCC	1866 ft/s (569m/s)
V50 - 9mm 127gr SXT (new)	1754 ft/s (534m/s)
P-BFS Avg. - 9mm 127gr SXT	24.6 mm
P-BFS Avg. - 40cal 165gr S+W Sp GDHP	27.2 mm
P-BFS Avg. - 5.7x28 27gr SS195	17 mm
P-BFS Avg. - 5.7x28 27gr SS197	19.3 mm



**SLATE
SOLUTIONS**

7060 W. State Road 84, Suite 12, Davie, FL 33317
info@SlateSolutions.com | SlateSolutions.com

754.200.6752